

Преглед

Приемане на Bluetooth 5.0 предаване и BLE (Bluetooth Low Energy) технология, EPEVER BLE RJ45 D позволява събиране на данни, комуникация, и безжично наблюдение на свързани устройства.



Характеристика

- Поддържа комуникация чрез телефонно ПРИЛОЖЕНИЕ
- Поддържа криптиране на данни
- Използвайте веднага след свързване; лесна и удобна работа
- Отличават се с бърза комуникация и силна способност против смущения
- Захранва се директно от комуникационния порт
- До 10 метра комуникационно разстояние
- Продукти, подходящи за приложението Solar Guardian:
XTRA, Triron, Tracer-AN(10-40A), Tracer-AN(50-100A), IPower-Plus, IPT, HPS-AL, HPS-AHL, UPower-Hi, Tracer-CPN

Съвместими продукти:

- Контролери: XTRA, Triron, Tracer-AN(10-40A), Tracer-AN(50-100A), Tracer-CPN
- Инвертори: IPower-Plus, IPT
- Инверторно зарядно устройство: HPS-AL, HPS-AHL, UPower-Hi

Parameter	Model	EPEVER BLE RJ45 D
Working voltage		5V ± 0.5V (Powered by RJ45 port)
Power consumption		Average: 5V@10mA; Peak: 5V@60mA
Communication distance		≤ 10m
Serial port baud rate		115200bps
Communication method		RS485 to Bluetooth
Connection port		RJ45
Bluetooth protocol		Bluetooth 5.0
Dimension (L x W x H)		63mm x 19mm x 13.8mm
Work temperature		-20°C~70°C
Enclosure		IP30
Net Weight		8.0g

Изтегляне на Solar Guardian



Google Play



Apple App Store

